3/4" Penny Rounds Mosaic - Gloss (12"x12" Sheet)









Dove Grey - DOG DEC360DOG34G



Off White - OFW DEC3600FW34G



Lagoon - LAG DEC360LAG34G



Cardinal - CAR DEC360CAR34G

3/4" Penny Rounds Mosaic - Matte (12"x12" Sheet)




White - WHI DEC360WHI34M




Beige - BEI DEC360BEI34M




Pumice - PUM DEC360PUM34M




Silver Sage - SIS DEC360SIS34M



Iron - IRO DEC360IRO34M



Shale - SHA DEC360SHA34M



Charcoal - CHA DEC360CHA34M





SIZING & PACKAGING

Туре	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Mosaic		DEC360•••34G	12"x12" Sheet	3/4" Penny Rounds Mosaic - Gloss	10	10.00
		DEC360•••34M	12"x12" Sheet	3/4" Penny Rounds Mosaic - Matte	10	10.00

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650	Bond Strength A137.2-7.7	Thermal Shock ASTM# C484
Results	N/A	7	≥ 250 lbf	≤ 0.5%	Unaffected	Pass	N/A

APPLICATIONS

Applications & ANSI Technical Specifications do not apply

	Floors	Walls	Countertops	Shower Floors (Matte Only)	Shower Walls	Pools/Spas
Residential	•	•	•	•	•	•
Commercial		•	•		•	•

LEGEND

- Product rated for Interior & Exterior use
- Product rated for Interior use only

* Special Order only

† May be suitable for Exterior Floors











The mesh backing on this tile has minimal glue to allow greater thinset coverage. To prevent the mosaics from falling off the mesh, keep the sheets as dry as possible while cutting. If necessary, place a light clear adhesive tape over the sheet while cutting to avert water. Install full sheets as much as possible. Fully embed 1/3 thickness of the tiles into the premium modified thinset.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes acceptance of the product. Reference the TCNA, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance Guide. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make product changes without notice. Please visit bedrosians.com for current product information.

