

1/2"x2" Herringbone Mosaic (11"x12 1/4" Sheet)



White - WHI
DEC90WHI122MO



Off White - OFW
DEC90OFW122MO



Putty - PUT
DEC90PUT122MO



Gray Haze - GRH
DEC90GRH122MO



Metallic - MET
DEC90MET122MO



Shadow - SHA
DEC90SHA122MO




Photo Features 1/2"x2" Herringbone Mosaic in White.






Photo Features 1/2"x2" Herringbone Mosaic in White.

SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Mosaic		DEC90***122MO	11"x12 1/4" Sheet	1/2"x2" Herringbone Mosaic	10	9.40

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650	Bond Strength A137.2-7.7	Thermal Shock ASTM# C484
Results	N/A	7	N/A	≤ 0.5%	Unaffected	N/A	N/A



APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◻	◻		◻	
Light Commercial		◻	◻		◻	
Commercial		◻	◻		◻	



LEGEND

- ☒ Product rated for Interior & Exterior use
- ☐ Product rated for Interior use only
- ☒ Applications & ANSI Technical Specifications do not apply
- ☐ Special Order only
- † May be suitable for Exterior Floors



The mesh backing on this tile has minimal glue to allow greater thinset coverage. To prevent the mosaics from falling off the mesh, keep the sheets as dry as possible while cutting. If necessary, place a light clear adhesive tape over the sheet while cutting to avert water. Install full sheets as much as possible. Fully embed 1/3 thickness of the tiles into the premium modified thinset.

Do not use chemicals containing chlorine.

Images and product samples are representative of a product's potential characteristics. There is no guarantee that the sample product or images will 100% match the product received. Field, mosaic, and trim tile may not be an exact match. Tiles are subject to variations in color, shade, size, surface texture and finish. Prior to installation, installer must blend tiles from several different boxes to achieve an even distribution of color range. Installer must conduct a dry mock layout under proper lighting conditions prior to installation. It is the consumer's responsibility to inspect the product prior to installation to ensure satisfaction. Once installed, the product is deemed accepted. Check Manufacturer's specifications as some Mosaic tiles may not be appropriate for wet applications. Reference the most current TCNA Handbook, ANSI, Manufacturer's specifications, and Bedrosians Care & Maintenance guide for installation, outdoor use, care and maintenance information. Improper installation, application, use, care and maintenance voids warranty. We reserve the right to make changes to product specifications at any time without notice. Please visit www.bedrosians.com for current product information.

MKTTERDEC90
REV. 8/2017

Bedrosians.com

