



## OAK PALAZZO BIANCO

Palazzo Bianco is a white stained floor with the strips laid in a Dutch Pattern. The floor is supplied in finished boards and installed in the same simple way as Kährs' other multi-layer parquet flooring. A certain amount of attention must be paid to the pattern when laying the floor.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	15313BEKWKW0	Wood Species	White Oak	Moisture content	EN13183	7%±2%
Surface Treatment	Matte finish	Design	Pattern	Minimum Mean Density kg/m <sup>3</sup>		>500 kg/m <sup>3</sup>
Refining Treatment	Brushed	Grading	Variation (Town)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	95 1/2" x 7 13/16" x 5/8"	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Weight per Package	51 lbs	Collection	European Renaissance Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	31.11 sq ft	Resandable	2 times	Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Area Per Board	5.188 sq ft	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
<b>DETAIL DESCRIPTION</b>		Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m2K/W)
Even colour with minor variations. Sapwood may occur. Small sized knots in limited numbers allowed.		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
<b>COLOUR CHANGE</b>		Floor heating	Yes	<b>CARB2</b>		Compliant
Stained product - noticeable color change over time.		Wear-layer material	Hardwood			
		Wear-layer thickness	1/8"			
		Core material	Pine/Spruce lamella			
		Thickness	5/8"			
		Installation method	Floating, glue-down			
		EAN Code	7393969037570			

### CERTIFICATE

