



OAK PALAZZO ROVERE

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	153138EK50KW0	Wood Species	White Oak	Moisture content	EN13183	7%±2%
Surface Treatment	Silk matte finish	Design	Pattern	Minimum Mean Density kg/m ³		>500 kg/m ³
Dimensions	95 1/2" x 7 13/16" x 5/8"	Grading	Variation (Town)	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package	51 lbs	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Area per Package	31.11 sq ft	Collection	European Renaissance Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area Per Board	5.188 sq ft	Resandable	2 times	Breaking Strength N/mm ²	EN1533	NPD
DETAIL DESCRIPTION		Natural/Stained	Natural	Thermal Conductivity	EN12664	0,14 W/mK
Even colour with minor variations. Sapwood may occur. Small sized knots in limited numbers allowed.		Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m2K/W)
COLOUR CHANGE		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
Some muting of colour variation to medium, straw brown.		Floor heating	Yes	CARB2		Compliant
		Wear-layer material	Hardwood			
		Wear-layer thickness	1/8"			
		Core material	Pine/Spruce lamella			
		Thickness	5/8"			
		Installation method	Glue-Down, floating			
		EAN Code	7393969024150			

CERTIFICATE

