

# HANDBÖRD

PRODUCT DESCRIPTION				
Article Number	151NDSEK06KW240			
Surface Treatment	Oil			
Refining Treatment	Beveled 4-sided, brushed, light smoked, handscraped, saw marks			
Dimensions	95 1/4" x7 3/8" x5/8"			
Weight per Package	49 lbs			
Area per Package	29.27 sq ft			
Area Per Board	4.878 sq ft			

### DETAIL DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

#### COLOUR CHANGE

Stained product - noticable color change over

FACTS	TECHNICAL PROPERTIES

5/8"

Floating, glue-down

7393969039079

Thickness

EAN Code

Installation method

Wood Species	White Oak	Moisture content	EN13183	7%±2%
Design	1-strip	Minimun Mean Density kg/m³		>500 kg/m³
Grading	Expressive	Reaction To Fire	EN13501-1	Dfl-s1
Range	Kährs Supreme	Formaldehyde Emission	EN717-1	E1
Collection	Småland Collection	Content PCP	CEN/TR14823	≤5 x 10-6n
Resandable	2 times	Breaking Strength Wmm²	EN1533	NPD
Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
Brinell Value	3,7	Thermal Resistance R-Value		.11 (m2K/W)
Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
Roor heating	Yes	CARB2		Compliant
Wear-layer material	Hardwood			
Wear-layer thickness	1/8"			
Core material	Pine/Spruce lamella			
Backside material	Veneer			

## CERTIFICATE

