



KINDA

Earth greys on a warm base, balanced contrast and transparency. Hard brushed, very rustic board with highlighted knots and cracks.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151NDSEK02KW240	Wood Species	White Oak	Moisture content	EN13183	7%±2%
Surface Treatment	Oil	Design	1-strip	Minimum Mean Density kg/m³		>500 kg/m³
Refining Treatment	Beveled 4-sided, handscraped, brushed, saw marks	Grading	Expressive	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	95 1/4" x 7 3/8" x 5/8"	Range	Kährs Supreme	Formaldehyde Emission	EN717-1	E1
Weight per Package	49 lbs	Collection	Småland Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	29.27 sq ft	Resandable	2 times	Breaking Strength N/mm²	EN1533	NPD
Area Per Board	4.878 sq ft	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
		Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m2KW)
		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
		Floor heating	Yes	CARB2		Compliant
		Wear-layer material	Hardwood			
		Wear-layer thickness	1/8"			
		Core material	Pine/Spruce lamella			
		Thickness	5/8"			
		Installation method	Floating, glue-down			
		EAN Code	7393969039031			
		Surface Color	Earth Grey			

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

The colour matures over time.

CERTIFICATE



AMERICAN RESOURCES BOARD