



SEVEDE

PRODUCT DESCRIPTION

Article Number	151NCSEK05KW240
Surface Treatment	Oil
Refining Treatment	Beveled 4-sided, brushed, light smoked, handscraped
Dimensions	95 1/4" x 7 3/8" x 5/8"
Weight per Package	49 lbs
Area per Package	29.27 sq ft
Area Per Board	4.878 sq ft

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Stained product - noticeable color change over time.

CERTIFICATE

FACTS

Wood Species	White Oak
Design	1-strip
Grading	Dynamic
Range	Kährs Supreme
Collection	Småland Collection
Resandable	2 times
Natural/Stained	Stained
Brinell Value	3, 7
Joint	Woodloc® 5S
Floor heating	Yes
Wear-layer material	Hardwood
Wear-layer thickness	1/8"
Core material	Pine/Spruce lamella
Backside material	Veneer
Thickness	5/8"
Installation method	Floating, glue-down
EAN Code	7393969039000

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³		>500 kg/m³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m2KW)
Biological Durability	EN350-2	Class 1
CARB2		Compliant

