



## VEDBO

| PRODUCT DESCRIPTION |                                       | FACTS                |                     | TECHNICAL PROPERTIES                   |             |                        |
|---------------------|---------------------------------------|----------------------|---------------------|--|-------------|------------------------|
| Article Number      | 151NCSEK01KW240                       | Wood Species         | White Oak           | Moisture content                       | EN13183     | 7%±2%                  |
| Surface Treatment   | Oil                                   | Design               | 1-strip             | Minimum Mean Density kg/m <sup>3</sup> |             | >500 kg/m <sup>3</sup> |
| Refining Treatment  | Beveled 4-sided, brushed, handscraped | Grading              | Dynamic             | Reaction To Fire                       | EN13501-1   | Dfl-s1                 |
| Dimensions          | 95 1/4" x 7 3/8" x 5/8"               | Range                | Kährs Supreme       | Formaldehyde Emission                  | EN717-1     | E1                     |
| Weight per Package  | 49 lbs                                | Collection           | Småland Collection  | Content PCP                            | CEN/TR14823 | ≤ 5 x 10-6n            |
| Area per Package    | 29.27 sq ft                           | Resandable           | 2 times             | Breaking Strength N/mm <sup>2</sup>    | EN1533      | NPD                    |
| Area Per Board      | 4.878 sq ft                           | Natural/Stained      | Natural             | Thermal Conductivity                   | EN12664     | 0,14 W/mK              |
|                     |                                       | Brinell Value        | 3, 7                | Thermal Resistance R-Value             |             | .11 (m2KW)             |
|                     |                                       | Joint                | Woodloc® 5S         | Biological Durability                  | EN350-2     | Class 1                |
|                     |                                       | Floor heating        | Yes                 | CARB2                                  |             | Compliant              |
|                     |                                       | Wear-layer material  | Hardwood            |  |             |                        |
|                     |                                       | Wear-layer thickness | 1/8"                |  |             |                        |
|                     |                                       | Core material        | Pine/Spruce lamella |  |             |                        |
|                     |                                       | Backside material    | Veneer              |  |             |                        |
|                     |                                       | Thickness            | 5/8"                |  |             |                        |
|                     |                                       | Installation method  | Floating, glue-down |  |             |                        |
|                     |                                       | EAN Code             | 7393969038966       |  |             |                        |

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

### COLOUR CHANGE

Some muting of colour variation to medium, straw brown.

### CERTIFICATE

