





WALL



Autumn 4" x 4" SEAATMW441P



Spring 4" x 4" SEASPRW441P



Summer 4" x 4" SEASUMW441P



Winter 4" x 4" SEAWTRW441P

DECO



Autumn Equinox 4" x 4" SEAATMEQNW441P



Autumn Solstice 4" x 4" SEAATMSOLW441P




Spring Equinox 4" x 4" SEASPREQNW441P



Spring Solstice 4" x 4" SEASPRWSOL441P





Eclipse 8" x 8" SEAECLF881P









Sa. Ft / Carton Pieces / Carton

n

WALL INSTALLATION	Thickness Grout Joint Recommendation		Shade Variation
	3/8″	1/4"	V2
WALL APPLICATIONS	Residential	Light Commercial	Commercial
Walls/Backsplashes	✓	✓	✓



floor installation	Thickness	Grout Joint Recommendation	Shade Variation
	5/16"	1/4"	V3
FLOOR APPLICATIONS	Residential	Light Commercial	Commercial
Walls/Backsplashes*	✓	✓	✓
Floors	✓	✓	✓

 $<sup>\</sup>hbox{``Suitable for exterior walls in freezing and non-freezing climats when proper installation methods are followed.}$ 

FLOOR TEST RESULTS	ASTM#	Results	NOTES	
Breaking Strength Surface Abrasion Chemical Resistance	C648 PEI C650	≥ 250 lbs 3 Resistant	Variations in shade, texture and edge profile are inherent in all glass, ceramic, porcelain and stone tiles. Always inspect product prior to	
DCOF	A.137.1	≥ 0.42	installation.	

