

PORCELAIN STONEWAY











PORCELAIN SIZES AND COLORS **COLORS**



Anthracite



Line Anthracite



White Anthracite

 $*2" \times 2"$ Mosaic (11-5/8" \times 11-5/8" Sheet) (Mesh-Mounted on a 12" x 12" Sheet)

12" x 24" Rectified

SIZES

*Only available in Anthracite, Beige and Grey



Beige



Line Beige



White Beige

Sq. Ft / Carton	Pieces / Carton
5.81	6
11.62	6



Grey



Line Grey



White Grey

PORCELAIN APPLICATIONS	Residential	Light Commercial	Commercial	Exterior
*Walls/Backsplashes	√ *	√ *	√*	√ *
Floors	✓	✓	\checkmark	
Shower Pan	√	√**	√**	
Pool Lining				
Countertops	✓	\checkmark	\checkmark	

^{*}Suitable for exterior wall applications in freezing and non-freezing climates, when proper installation methods are followed. **Applies to $2" \times 2"$ Mosaic only.

PORCELAIN INSTALLATION	Thickness	Grout Joint Recommendation	Shade Variation
	3/8″	1/4"	V3

^{*}Large format and rectangular wall tile require specific attention during installation. In view of ANSI and manufacturing tolerances, it is understood that no more than 33% offset should be used for installation.

TEST RESULTS	ASTM#	Unpolished Result	NOTES
Water Absorption	C373	≤ 0.5%	Variations in shade, texture and
Breaking Strength	C648	≥ 400lbs	edge profile are inherent in all
Scratch Hardness	MOHS	6	glass, ceramic, porcelain and stone tiles. Always inspect product
Chemical Resistance	C650	Resistant	prior to installation.
Wet DCOF	A.137.1	≥ 0.42	

