

MANOR OAK

Awhite washed handscraped product, may contain knots and cracks. Grande products may continue to develop their rustic nature after the floor has been installed; splits and cracks that occur after installation are normal and should be considered part of the timbers natural character. This product must be oiled after installation and prior to use.

Article Number	201XABEKFVKE280
Surface Treatment	Oil
Refining Treatment	Beveled 4-sided, brushed, handscraped
Dimensions	110 1/4" x 10 1/4" x 3/4"
Weight per Package	84 lbs
Area per Package	31.32 sq ft
Area Per Board	7.836 sq ft
	RIPTION

Naturally occuring wood colour variations				
allowed, from light to dark brown. The product				
includes large sound and black knots. Knots				
may vary in size and numbers.				

COLOUR CHANGE

Stained product - noticable color change over time.

FACTS		
Wood Species	White Oak	
Design	1-strip	
Grading	Variation (Town)	
Range	Kährs Supreme	
Collection	Grande Collection	
Resandable	2 times	
Natural/Stained	Stained	
Joint	Tongue & Groove	
Roor heating	No	
Wear-layer material	Hardwood	
Wear-layer thickness	1/5"	
Backside material	Veneer	
Thickness	3/4"	
Installation method	Glue-Down, floating	
EAN Code	7393969031523	
Surface Color	White	

TECHNICAL PROPERTIES

Moisture content EN13183 7%±2% Minimun Mean Density kg/m³ >500 kg/m³ Reaction To Fire EN13501-1 Dfl-s1 Formaldehyde Emission EN717-1 E1 Content PCP CEN/TR14823 ≤ 5 x 10-6n Breaking Strength N/mm² EN1533 NPD Thermal Conductivity EN12664 0,14 W/mK Thermal Resistance R-Value .14 (m2K/W) Biological Durability EN350-2 Class 1 CARB2 Compliant			
Reaction To Fire EN13501-1 Dfl-s1 Formaldehyde Emission EN717-1 E1 Content PCP CEN/TR14823 ≤ 5 x 10-6n Breaking Strength N/mm² EN1533 NPD Thermal Conductivity EN12664 0,14 W/mK Thermal Resistance R-Value .14 (m2K/W) Biological Durability EN350-2 Class 1	Moisture content	EN13183	7%±2%
Formaldehyde Emission EN717-1 E1 Content PCP CEN/TR14823 ≤ 5 x 10-6n Breaking Strength Wmm² EN1533 NPD Thermal Conductivity EN12664 0,14 W/mK Thermal Resistance R-Value .14 (m2K/W) Biological Durability EN350-2 Class 1	Minimun Mean Density kg/m³		>500 kg/m³
Content PCP CEN/TR14823 ≤ 5 x 10-6n Breaking Strength N/mm² EN1533 NPD Thermal Conductivity EN12664 0,14 W/mK Thermal Resistance R-Value .14 (m2K/W) Biological Durability EN350-2 Class 1	Reaction To Fire	EN13501-1	Dfl-s1
Breaking Strength N/mm² EN1533 NPD Thermal Conductivity EN12664 0,14 W/mK Thermal Resistance R-Value .14 (m2K/W) Biological Durability EN350-2 Class 1	Formaldehyde Emission	EN717-1	E1
Thermal Conductivity EN12664 0,14 W/mK Thermal Resistance R-Value .14 (m2K/W) Biological Durability EN350-2 Class 1	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Thermal Resistance R-Value .14 (m2K/W) Biological Durability EN350-2 Class 1	Breaking Strength N/mm²	EN1533	NPD
Biological Durability EN350-2 Class 1	Thermal Conductivity	EN12664	0,14 W/mK
	Thermal Resistance R-Value		.14 (m2K/W)
CARB2 Compliant	Biological Durability	EN350-2	Class 1
	CARB2		Compliant

CERTIFICATE

