# STAINLESS STEEL N X G = N FLOW CONTROL DURABILITY PERFORMANCE Setup and Use

Rotate float assembly as shown in images below. The float assembly can be adjusted to any water level from 4" to 9" by sliding the float assembly up or down the vertical pipe as shown below. Rotating or rocking the float assembly on the vertical pipe will allow for easier adjustment of height by applying pressure in the direction needed.










\*Install water hose hand tight into the brass swivel. If the swivel remains loose with play side to side and is able to rotate easily, remove and check the hose end for damaged threads. Damaged hose threads will prevent the face of the hose fitting from sealing against the water hose washer located in the swivel.


# **Profile Selection**

Regardless of the style pool deck you have the new STAYPOOLLIZER 2.0 can be configured simply with no tools required. Rotation of the rear legs allows this unique design to accommodate many of today's modern pool designs.









# Water Level Setting

We recommend setting the float assembly height so the bottom edge of the float assembly is the same height as the center of your skimmer inlet. This should provide adequate water level for most pools. Final adjustments can be made should you desire a different water level.

### Water Faucet Setting

Reduce water flow to no more than a steady stream out of the faucet.

- •In the unlikely event of water hose failure, reducing the flow will minimize water loss.
- Filling operation will be quieter.
- •Unit may continuously run, if your pool loses water. (THIS IS NORMAL, most pools lose 1/4"- 1/2" per day.)

Test unit for proper operation by lifting upward on the float while the water is on. All water flow stops while the float is lifted and flows when float is down.

- •Automatic operation replaces water as it's lost, never overfilling your pool.
  - \*Reduced water flow is adequate to keep the average pool full now that the Staypoollizer controls the water level 24/7.

Safety Warning



AVOID PLACEMENT IN AREAS WHERE FOOT TRAFFIC IS LIKELY TO OCCUR. KEEP ATTACHED WATER HOSE LAYING FLAT AT ALL TIMES. REMOVE PRODUCT FROM POOL DECK DURING SOCIAL GATHERINGS TO REDUCE POSSIBLE INJURY TO OTHERS.

# Limited One Year Factory Warranty

JCS Industries LLC warrants its products (with exceptions as indicated), to the original purchaser, to be free of defects for a period of one year from the date of purchase. This limited warranty covers all parts against defects or breakage in normal intended use. The warranty does not cover any damage caused by accidental dropping, rough handling, or misuse of the product. Altering or tampering with the product will also void this warranty.




# For purchasing our product

Are you happy with our product?











We appreciate your business and welcome you to our long list of satisfied and much valued customers. By reviewing our products you help other customers make informed purchase decisions and are a great source of suggestions about how to improve our product line. Authentic customer reviews help new customers find and evaluate our products before purchasing. Our success comes from continued faith in the excellent of our products and service, something we are 100% dedicated in providing. We know you had plenty of options while shopping for a automatic pool water fillers, and we are honered that you have chosen the Staypoollizer.

Looking forward to your business again in the future.

Thanks again,

Allison L.

Do you have any additional comments, questions, or concerns you would like to share?



Email us at : contact@jcscoinc.com www.staypoollizer.com

