

Specs

Output	20W	50W
Total Lumens	309-320	430-465
Input Voltage	10-15V	10-15V
Input Power (W)	4.0	6.0
VA	6.2	9.2
Efficacy (Lumens per Watt)	91-94	94-100
Color Rendering Index (CRI)	87	86
Center Beam Candlepower	541-965	801-1,154
Dimming	Phase	Phase
RGBW Available	No	No
Minimum Rated Life (L70)	30,000 Hrs	30,000 Hrs

 [Translate](#)

[LED MR-16 Eco Model Specs \(/node/48641\)](/node/48641)

Model No.	Description	Watts	Va	Equivalent Wattage	CCT	Beam Spread	Total Lumens	CBCP	CRI	Efficacy
MR16ECO20WFL	Flood	4W	6.2	20W	2700K	35°	320	965	87	91
MR16ECO20WWF	Wide Flood	4W	6.2	20W	2700K	60°	309	541	87	94
MR16ECO50WFL	Flood	6W	9.2	50W	2700K	35°	465	1,154	86	92
MR16ECO50WWF	Wide Flood	6W	9.2	50W	2700K	60°	430	801	86	100

[Cookies Settings](#)
[Accept All Cookies](#)

[MR-16 Eco Dimensions \(/node/48631\)](/node/48631)

By clicking "Accept All Cookies", you agree to the storing of cookies on your device to enhance site navigation, analyze site usage, and assist in our marketing efforts.

[Privacy Policy \(https://www.hunterindustries.com/privacy-policy\)](https://www.hunterindustries.com/privacy-policy)