



11003

ProPlus™ 11003 Rotor

Appropriate for medium to large landscape areas with high level risers and shrubs.

Direct replacement for the Toro Super800.

Features:

- Gear driven, rotary type sprinkler capable of covering an area of 22' to 50'.
- Revolutionary patented easy arc set is easily adjusted from the top with a flat blade screwdriver. Stainless steel radius adjustment screw.
- 2N1 adjustable or continuous rotation provides a full range of adjustments from 40° to a full 360°. Patented arc set degree markings show the degree of adjustment with the point of an arrow on the top cover.
- Arc memory clutch returns rotor to its preset position automatically even after being tampered with. Time proven patented reversing mechanism assures continuous reverse and return.
- Ratcheting riser easily adjusts your left start position by turning the riser.
- Supplied with 9 numerically coded interchangeable nozzles including 4 low angle nozzles. Wide selection of nozzles provides flexibility in system design to achieve matched precipitation.
- Heavy duty rubber cover seals our dirt and increases durability.
- **FULL 5 YEAR WARRANTY. Subject to all standard warranty conditions that apply to all K-Rain rotors.**



Specifications:

- Inlet 3/4" threaded NPT
- Arc Adjustment Range: 40° to continuous 360°
- Flow range: 0.5 - 10.0 GPM
- Pressure Rating: 20-70 PSI
- Precipitation Rate: 0.06 to 0.50 inches/hour (depending on spacing and nozzle used)
- Overall height popped down : 7 1/2" 17" for High pop
- Recommended spacing: 28' to 44'
- Radius: 22' to 50'
- Nozzle trajectory: 26° standard or 12° low angle
- Riser Height: 5"



ARC selection 40° to continuous 360°. Adjusts from LEFT start.

Find performance data on following page.

Part Number	Description	Ctn Qty	List Price
11003	ProPlus mid-range rotor	20	\$ 22.97
11003-SH	ProPlus shrub head	20	23.54

K-Rain products are not available for sale in NC, SC, TN, or MA.



www.americangranby.com
 In the United States: Phone (800) 776-2266 Fax (800) 729-3299
 In Canada: Phone (800) 268-7570 Fax (905) 629-3204

2/20/18