

ROAM XL

Range: **Up to 2 miles**
Type: **Remote**

FEATURES

- Works with Hunter X-Core, Pro-C, PCC, Pro-C Hydrwise, ICC2, HCC, I-Core, ACC, and ACC2 controllers through a SmartPort connection
- Up to 2 miles (line of sight) range for remote manual operation of Hunter irrigation systems
- Operate up to 240 stations
- 128 different programmable addresses
- Display shows remaining battery life
- Programmable run times: 1 to 90 minutes
- Large LCD display, push-button operation
- Manually run watering cycles without modifying regular program
- Rugged plastic carrying case included
- Warranty: 3 years

REMOTE SPECIFICATION

- Transmitter power source: 4 AAA batteries included
- Receiver power source: 24 VAC, from controller through a SmartPort connector
- System operating frequency: 27 MHz band
- SmartPort connector can be mounted up to 50' (max.) from controller (use ROAM-SCWH shielded cable wiring harness)
- FCC approved: No FCC license required

* Not available in all countries.



Roam XL (no antenna)

Height: 6¼"
Width: 3"
Depth: 1¼"



SmartPort

Hunter remotes require the installation of a SmartPort wiring harness. The SmartPort is a connector that is wired to the terminals on the controller, and allows quick connection to any Hunter receiver.



Wall Mount Bracket for SmartPort

P/N 258200

ROAM XL	
Model	Description
ROAMXL-KIT	Transmitter, receiver, SmartPort wiring harness, 4 AAA batteries and plastic carrying case included
ROAMXL-TR	Handheld transmitter, and 4 AAA batteries included
ROAMXL-R	Receiver unit (SmartPort wiring harness included)

OPTIONS (SPECIFY SEPARATELY)	
Model	Description
258200	Wall Mount Bracket for SmartPort
ROAMXL-CASE	Plastic carrying case
ROAM-WH	SmartPort wiring harness (length: 6')
ROAM-SCWH	Shielded SmartPort wiring harness (length: 25')

CONTROLLER ACCESSORIES