



**ARTHUR
ENTERPRISES**

Technical Specifications

Super Tree Tie

DESCRIPTION:

Super Tree Tie is nylon reinforced vinyl. It's acid resistant and waterproof. It has tremendous strength (tensile strength: 256 Lbs; bursting strength: 395 lbs. p.s.i.).

TECHNICAL DATA:

Thickness:	16 mm
Weight:	12 oz/sq. yd.
Tensile (lbs/grab method):	256 (warp) 266 (fill)
Tears (lbs/tongue method):	91 (warp) 95 (fill)
Burst (lbs/psi)	395
Chemical Name:	Plasticized poly-vinyl Chloride Film
Trade Name:	PVC Sheeting
Chemical Family:	Compound of PVC, ester. plasticizer and minor Ingredients
Hazardous Materials:	NA
Specific Gravity:	1.20 - 1.70
Percentage Volatile:	<7%
Evaporation Rate:	NA
Width:	1"
Flame Point:	ASTM D-1929
Extinguishing Media:	Water, Dry Chemical Co2
Special Fire Fighting Procedures:	Wear self-contained breathing apparatus and preventive clothing to prevent contact with skin and eyes.
Effects of Evaporation:	Non-Expected
Incapability:	Oxidizing materials can cause a reaction
Hazardous Decomposition : Products	HC2, CO, CO2, Benzene, Aromatic & Aliphatic Hydrocarbon
Ventilation:	None Should be Needed
Precautions to be taken Handing and Storing:	Use Applicable fire and safety code precautions for warehouse sprinklers Registered Flame Resistant Product.

Arthur Enterprises

5181 Argosy Avenue
Huntington Beach, CA
92649

Phone:
(714) 898-1311

Fax:
(714) 898-3399

EVillanueva@Harrisind.com

Information is provided by manufacturer and is on file.