FXLuminaire.



The simple and chic design of the SC seamlessly integrates in any landscape and complements many architectural styles. With LED efficiency and durable construction, the SC path light is built to last.

SC: Path Light

NUMBER OF LEDS:	1
HALOGEN LUMEN OUTPUT EQUIVALENT:	10 Watt
USEFUL LED LIFE (L70):	50,000 hrs avg
INPUT VOLTAGE:	10 to 15V
VA TOTAL: (Use this number to size the transformer)	2.4
WATTS USED:	2.0
LUMENS PER WATT (EFFICACY)	19.4
MAX LUMENS:	39
CCT (Ra)	86





SC: Path Light

FACTORY INSTALLED OPTIONS (TOP ASSEMBLY): Order 1 + 2

Step	Description	Code
1	TOP ASSEMBLY	SCLEDTA
2	TOP FINISH	AB*, AT*, CU, NP*, WG, FW, AL, BZ, DG, WI, VF, SB, FB

EXAMPLE: SCLEDTA-NP = SC Top Assembly - Nickel Plate Finish

FACTORY INSTALLED OPTIONS (RISER ASSEMBLY): Order 1 + 2 (optional) + 3 + 4 + 5

Step	Description	Code
1	RISER TYPE	Р
2	OPTIONAL ZD	ZD (Refer to the Luxor page in the Lighting Control section)
3	LAMP	1LED (50,000 avg. life hours)
4	RISER HEIGHT	8RA, 12RA, 18RA, 24RA, 36RA (in inches)
5	FINISH	AB*, AT*, CU, NP*, WG, FW, AL, BZ, DG, WI, VF, SB, FB

EXAMPLE: P-ZD-1LED-24RA-NP = Riser Type - ZD Option - 1 LED Board - 24" Riser - Nickel Plate Finish

FIELD INSTALLED OPTIONS: Order Individually

Mounting Options	43	44		w
Long Slot Spike (250015840000) 2.5" x 10" Included		V	V	
Super Slot Spike (753900) 2" x 10"	T		V	- 1
SuperJ-Box (<i>SJ-XX**</i>) 2.5" x 12"	₩	₩	₩.	
Post Mount (<i>PM-XX**</i>) 2.5" x 13"	Long Slot Spike	Super Slot Spike	Super J-Box XX**	Post Mount XX**

EXAMPLE: 753900 = Super Slot Spike

PHOTOMETRICS:



Beam angle is calculated using LM-79 method for SSL Luminaires:

METALS



AB = Antique Bronze* (On Copper/Brass)



AT = Antique Tumbled* (On Copper/Brass)



 $\mathbf{CU} = \mathsf{Copper}$



NP = Nickel Plate*

POWDER COAT



WG = White Gloss



FW = Flat White



AL = Almond



BZ = Bronze Metallic





DG = Desert Granite



WI = Weathered Iron



VF = Verde Speckle





SB = Sedona Brown



FB = Flat Black

The SC includes a 1LED board, and choice of riser size and finish, 3 ft. lead wire and Long Slot Spike.



All SC path lights come standard with amber, green, blue and frosted filters

Note: Only the copper portions of the path lights are powder coated. The brass pieces remain natural.

^{**} Denotes finish code



 $[&]quot;Beam \, angle \, is \, defined \, as \, two \, times \, the \, \, vertical \, angle \, at \, which \, the \, intensity \, is \, 50\% \, of \, the \, maximum."$

^{*} May require longer lead time