


LINEAR PENDANT LAMP - EU VERSION

THOMAS BENTZEN ON THE DESIGN "The Linear Lamp Series is designed from the idea of creating smaller atmospheres through modern light, bringing a sense of intimacy to larger spaces. With their elegant expression, subtle details and inherent functionality of a dimmable light source, the designs create space for both being and working on your own as well as making for a friendly environment when in the company of others. Use the Linear Lamp Series for any space in need of modern, functional lighting that can be adjusted to the exact purpose of your space."









DESIGNED BY / YEAR OF DESIGN

Thomas Bentzen / 2020

ABOUT THE DESIGNER

Thomas Bentzen is a Copenhagen-based designer, working to infuse his designs with a refined simplicity. His studio was founded in 2010, creating designs that have received international recognition at fairs and exhibitions all over the world.

CATEGORY

Pendant lamp

ENVIRONMENT

Indoor

DESCRIPTION

An elegant lamp, designed with simple lines and dimmable light source.

MATERIAL

Lamphead in pressure-die casted and extruded, powder coated aluminum. Stem in powder coated steel. Diffuser in polycarbonate. PVC cord.

CORD & WIRE LENGTH

400 cm / 157.5"

BULB INCLUDED

Yes. Integrated LED.

CEILING CAP INCLUDED


Yes, white.

DIMMABLE FUNCTION

Yes. The Linear Pendant Lamp is designed for phase cut dimming with standard leading edge dimmers (TRIAC).

CLEANING AND CARE

Clean with soft dry cloth only. Always switch off electricity supply before cleaning.




LINEAR PENDANT LAMP - EU VERSION












changed in the luminaire. 20,3 kWh/1000h

874/2012



LINEAR PENDANT LAMP 169.2 CM

LAMP RATING

Voltage 220-240V Frequency 50/60Hz IP Rating IP2O Classification

Socket Integrated, non-replaceable LEDs

BULB SPECIFICATION - 87,2 CM / 34.3"

Integrated,

non-replaceable LEDs

20.3 W Watt 1060 lm Luminous flux Color temperature 3000 K

Color consistency 3 McAdam steps

Lumen

maintenance (70%) 48.000h CRI 90 Dimmable Yes Risk Group Except

BULB SPECIFICATION - 169,2 CM / 66.6"

Item Integrated,

non-replaceable LEDs

37.7 W Watt 1880 lm Luminous flux Color temperature 3000 K Color consistency 3 McAdam steps

Lumen

maintenance (70%) 48.000h CRI 90 Dimmable Yes Risk Group Except

AS/NZS 6O598.2.I

GENERAL STANDARDS & CERTIFICATES

AUS/NZL UK CE (Low Voltage Directive - 2014/35/EU) AS/NZS 60598.1 and

IEC 6O598-I (EU deviations) IEC 6O598-2-I (EU deviations)

Electromagnetic Compatibility (EMC) Directive - 2014/30/EU

ROHS Directive - 2011/65/EU amended RoHS 3 Directive 2015/863

ECO Design Directive - 2009/125/EC

WEEE Directive - 2012/19/EU

REACH Directive - EC/I9O7/2OO6

BS 4533-IO2.I, EN 6O598-2-I

Electrical Equipment (Safety) Regulations 2016 Electromagnetic Compatibility Regulations 2016

The Restriction of the Use of Certain Hazardous Substances in

Electrical and Electronic Equipment Regulations 2012

The Ecodesign for Energy-Related Products and Energy Information

(Amendment) (EU Exit) Regulations 2019

MUUTO