



Seamless Fabric Wall Covering Installation Instructions

Tools Needed

- Sponge
- Pencil
- Smoothing Tool
- Plumb Line / Spirit Level
- Roller & Tray
- Steel Spatula
- Wallpaper Knife
- Sandpaper
- Scraper
- Wallpaper Paste

Preparations

- Wallpaper paste is required for this material.
- This wall covering is made to be installed as a single seamless panel. The printable height of this material is up to 124". It is recommended to get a friend or second person to help install.
- Clear furniture & other obstructions from work area.
- Clean wall with lightly damp cloth using tap water to ensure it is free of dust and debris. Do not use chemicals.
- Wall should be smooth and clean. Sand any rough areas, if necessary. Prime if it has not been previously painted.
- Turn off breaker to any electricity running to the wall you are installing on (only required for when installing around outlets or light switches). Remove & cover exposed outlets or switches to protect them from getting wet.
- Cover your flooring with tarp or absorbent drop cloth, if necessary.

Seamless Installation

- Unroll the wall covering. Ensure that it will cover the entire area per the measurements you supplied when ordering. Lay it flat for a few minutes to let it uncurl.
- Draw a plumb line down the left hand corner of your wall as a guide to align the left edge of the wall covering.
- Apply the paste generously and evenly to the entire wall area using a paint roller. Make sure the paste does not dry out -- if necessary add a pint of water per gallon.
- Make sure that the wall covering design is both vertically plumb and horizontally level when applying to the wall.
- Carefully smooth out bubbles and creases using a smoothing tool from the middle out to the edges. Be sure to keep the tool clean at all times

- Use a damp sponge to clean the surface from any paste residue.
- After the wall covering and adhesive has dried, trim the top and bottom and around any framework – Ensure that the wall covering is pushed into the corners and edges before trimming the excess. Steel rules or spatulas are ideal for neat and straight cuts. Replace your knife blade often.

Removal

- Beginning at the top pull the wall covering back on itself at an angle until it is completely removed.
- Use a damp sponge to remove any paste residue once removal is completed.