



Technical Specifications

Description Plank Size 7" Wide x 48" Long (Wood Grain Texture) Size / Thickness 4.7mm Total Thickness (3.7mm Core + 1.0mm EVA) 12 mil Wearlayear Quality 1st quality, natural color variation, free of structural defects Installation 2G Click System - Floating Warranty Lifetime Residential Wear Warranty Line Lifetime Waterproof Warranty United Lifetime Waterproof Warranty Linited Lifetime Waterproof Warranty Wear Resistance (EN13329) ≥ 4000 cycles - Classification (Class 34) Impact Resistance (EN13329) ≥ 1800mm - Classification (Class 34) Micro-scratch Resistance ISO 1518-1 - ≥ 3200g Static Load (250-BS/115KG) ASTM F970 - 15 - Class 4 Heavy Commercial Impact Sound Reduction (IIC) IIC: 59 Locking Strength Long side ≥ 6.3km/m Short Side ≥ 5.4km/m Resistance to staining No visible change with 10 minute duration of contact (Water, acetone, cleaning solution, coffee, sodium hydroxide(NaOH), hydrogen peroxide (HcOz), shoe polish. Fire Risistence ASTM E648/662 - 1.09 W/cm2 - Class 1 FloorScore® SCS-FS-04026 I 2020.06.01 - 2021.05.31 Packaging Content of Box (7" x 48" - 21.27 Sq.Ft/Box)	Characteristics	Luxury RigidCore Plank Floating Floor with IXPE Underlayment and 2G Superior click system
Quality 1st quality, natural color variation, free of structural defects Installation 2G Click System - Floating Warranty Lifetime Residential Wear Warranty Lifetime Structural Warranty Limited Lifetime Waterproof Warranty 10 Year Limited Light Commercial Warranty Wear Resistance (EN13329) ≥ 4000 cycles - Classification (Class 34) Micro-scratch Resistance ISO 1518-1 - ≥ 3200g Static Load (250>BS/115KG) ASTM F970 - 15 - Class 4 Heavy Commercial Impact Sound Reduction (IIC) IIC: 59 Locking Strength Long side ≥ 6.3km/m Short Side ≥ 5.4km/m Resistance to staining No visible change with 10 minute duration of contact (Water, acetone, cleaning solution, coffee, sodium hydroxide(NaOH), hydrogen peroxide (HcOz), shoe polish. Fire Risistence ASTM E648/662 - 1.09 W/cm2 - Class 1 Fungi Resistance ASTM G21-15 Unlike Cork, this product shows zero "None" results for observed growth. Packaging Content of Box (7" x 48" - 21.27 Sq.Ft./ Box)	Description	Plank Size 7" Wide x 48" Long (Wood Grain Texture)
Installation 2G Click System - Floating	Size / Thickness	4.7mm Total Thickness (3.7mm Core + 1.0mm EVA) 12 mil Wearlayear
Warranty Lifetime Residential Wear Warranty Lifetime Structural Warranty Limited Lifetime Structural Warranty 10 Year Limited Lifetime Waterproof Warranty 10 Year Limited Lifetime Waterproof Warranty Wear Resistance (EN13329) ≥ 4000 cycles - Classification (Class 34) Impact Resistance (EN13329) ≥ 1800mm - Classification (Class 34) Micro-scratch Resistance ISO 1518-1 - ≥ 3200g Static Load (250>BS/115KG) ASTM F970 - 15 - Class 4 Heavy Commercial Impact Sound Reduction (IIC) IIC: 59 Locking Strength Long side ≥ 6.3km/m Short Side ≥ 5.4km/m No visible change with 10 minute duration of contact (Water, acetone, cleaning solution, coffee, sodium hydroxide(NaOH), hydrogen peroxide (H±O2), shoe polish. Fire Risistence ASTM E648/662 - 1.09 W/cm2 - Class 1 Fungi Resistance ASTM G21-15 Unlike Cork, this product shows zero "None" results for observed growth. Packaging Content of Box (7" x 48" - 21.27 Sq.Ft/ Box)	Quality	1st quality, natural color variation, free of structural defects
Warranty Lifetime Structural Warranty Limited Lifetime Waterproof Warranty 10 Year Limited Light Commercial Warranty Wear Resistance (EN13329) ≥ 4000 cycles - Classification (Class 34) Impact Resistance (EN13329) ≥ 1800mm - Classification (Class 34) Micro-scratch Resistance ISO 1518-1 - ≥ 3200g Static Load (250>BS/115KG) ASTM F970 - 15 - Class 4 Heavy Commercial Impact Sound Reduction (IIC) IIC: 59 Locking Strength Long side ≥ 6.3kn/m Short Side ≥ 5.4kn/m Resistance to staining No visible change with 10 minute duration of contact (Water, acetone, cleaning solution, coffee, sodium hydroxide(NaOH), hydrogen peroxide (H±O2), shoe polish. Fire Risistence ASTM E648/662 - 1.09 W/cm2 - Class 1 Fungi Resistance ASTM G21-15 Unlike Cork, this product shows zero "None" results for observed growth. FloorScore® SCS-FS-04026 I 2020.06.01 - 2021.05.31 Packaging Content of Box (7" x 48" - 21.27 Sq.Ft/ Box)	Installation	2G Click System - Floating
Impact Resistance (EN13329) ≥ 1800mm - Classification (Class 34) Micro-scratch Resistance ISO 1518-1 - ≥ 3200g Static Load (250>BS/115KG) ASTM F970 - 15 - Class 4 Heavy Commercial Impact Sound Reduction (IIC) IIC: 59 Locking Strength Long side ≥ 6.3kn/m Short Side ≥ 5.4kn/m Resistance to staining No visible change with 10 minute duration of contact (Water, acetone, cleaning solution, coffee, sodium hydroxide(NaOH), hydrogen peroxide (HzOz), shoe polish. Fire Risistence ASTM E648/662 - 1.09 W/cm2 - Class 1 Fungi Resistance ASTM G21-15 Unlike Cork, this product shows zero "None" results for observed growth. FloorScore® SCS-FS-04026 I 2020.06.01 - 2021.05.31 Packaging Content of Box (7" x 48" - 21.27 Sq.Ft./ Box)	Warranty	Lifetime Structural Warranty Limited Lifetime Waterproof Warranty
Micro-scratch Resistance ISO 1518-1 - ≥ 3200g Static Load (250>BS/115KG) ASTM F970 - 15 - Class 4 Heavy Commercial Impact Sound Reduction (IIC) IIC: 59 Locking Strength Long side ≥ 6.3kn/m Short Side ≥ 5.4kn/m Resistance to staining No visible change with 10 minute duration of contact (Water, acetone, cleaning solution, coffee, sodium hydroxide(NaOH), hydrogen peroxide (H≥O₂), shoe polish. Fire Risistence ASTM E648/662 - 1.09 W/cm2 - Class 1 Fungi Resistance ASTM G21-15 Unlike Cork, this product shows zero "None" results for observed growth. FloorScore® SCS-FS-04026 2020.06.01 - 2021.05.31 Packaging Content of Box (7" x 48" - 21.27 Sq.Ft./ Box)	Wear Resistance (EN13329)	≥ 4000 cycles - Classification (Class 34)
Static Load (250>BS/115KG) ASTM F970 - 15 - Class 4 Heavy Commercial Impact Sound Reduction (IIC: 59 Locking Strength Long side ≥ 6.3kn/m Short Side ≥ 5.4kn/m Resistance to staining No visible change with 10 minute duration of contact (Water, acetone, cleaning solution, coffee, sodium hydroxide(NaOH), hydrogen peroxide (H±O₂), shoe polish. Fire Risistence ASTM E648/662 - 1.09 W/cm2 - Class 1 Fungl Resistance ASTM G21-15 Unlike Cork, this product shows zero "None" results for observed growth. FloorScore® SCS-FS-0402612020.06.01 - 2021.05.31 Packaging Content of Box (7" x 48" - 21.27 Sq.Ft./ Box)	Impact Resistance (EN13329)	≥ 1800mm - Classification (Class 34)
Impact Sound Reduction (IIC) IIC: 59 Locking Strength Long side ≥ 6.3kn/m Short Side ≥ 5.4kn/m Resistance to staining No visible change with 10 minute duration of contact (Water, acetone, cleaning solution, coffee, sodium hydroxide(NaOH), hydrogen peroxide (H±O₂), shoe polish. Fire Risistence ASTM E648/662 - 1.09 W/cm2 - Class 1 Fungi Resistance ASTM G21-15 Unlike Cork, this product shows zero "None" results for observed growth. FloorScore® SCS-FS-04026 I 2020.06.01 - 2021.05.31 Packaging Content of Box (7" x 48" - 21.27 Sq.Ft./ Box)	Micro-scratch Resistance	ISO 1518-1 - ≥ 3200g
Locking Strength Long side ≥ 6.3kn/m Short Side ≥ 5.4kn/m Resistance to staining No visible change with 10 minute duration of contact (Water, acetone, cleaning solution, coffee, sodium hydroxide(NaOH), hydrogen peroxide (H₂O₂), shoe polish. Fire Risistence ASTM E648/662 - 1.09 W/cm2 - Class 1 Fungi Resistance ASTM G21-15 Unlike Cork, this product shows zero "None" results for observed growth. FloorScore® SCS-FS-04026 2020.06.01 - 2021.05.31 Packaging Content of Box (7" x 48" - 21.27 Sq.Ft./ Box)	Static Load (250>BS/115KG)	ASTM F970 - 15 - Class 4 Heavy Commercial
Short Side ≥ 5.4kn/m Resistance to staining No visible change with 10 minute duration of contact (Water, acetone, cleaning solution, coffee, sodium hydroxide(NaOH), hydrogen peroxide (H₂O₂), shoe polish. Fire Risistence ASTM E648/662 - 1.09 W/cm2 - Class 1 Fungi Resistance ASTM G21-15 Unlike Cork, this product shows zero "None" results for observed growth. FloorScore® SCS-FS-04026 2020.06.01 - 2021.05.31 Packaging Content of Box (7" x 48" - 21.27 Sq.Ft./ Box)	_	IIC: 59
hydroxide(NaOH), hydrogen peroxide (H2O2), shoe polish. Fire Risistence ASTM E648/662 - 1.09 W/cm2 - Class 1 Fungi Resistance ASTM G21-15 Unlike Cork, this product shows zero "None" results for observed growth. FloorScore® SCS-FS-04026 2020.06.01 - 2021.05.31 Packaging Content of Box (7" x 48" - 21.27 Sq.Ft./ Box)	Locking Strength	
Fungi Resistance ASTM G21-15 Unlike Cork, this product shows zero "None" results for observed growth. FloorScore® SCS-FS-04026 2020.06.01 - 2021.05.31 Packaging Content of Box (7" x 48" - 21.27 Sq.Ft./ Box)	Resistance to staining	
ASTM G21-15 FloorScore® SCS-FS-04026 2020.06.01 - 2021.05.31 Packaging Content of Box (7" x 48" - 21.27 Sq.Ft./ Box)	Fire Risistence	ASTM E648/662 - 1.09 W/cm2 - Class 1
Packaging Content of Box (7" x 48" - 21.27 Sq.Ft./ Box)	_	Unlike Cork, this product shows zero "None" results for observed growth.
Content of Box (7" x 48" - 21.27 Sq.Ft./ Box)	FloorScore®	SCS-FS-04026 2020.06.01 - 2021.05.31
	Packaging	
	Content of Box	(7" x 48" - 21.27 Sq.Ft./ Box)
Content of Pallet (65 cartons - 2149.50 lbs)	Content of Pallet	(65 cartons - 2149.50 lbs)