

STANTON

CARPET ♦ CUSTOM RUGS ♦ RUNNERS

Natural Beauty Series Max 9 – Decorative WPC Specification Style: Saybrook - Hartford

Specifications

Construction

Total Thickness

Wear Layer Thickness

Locking System

Edge Treatment

Faces/Embossing/Gloss

Size

Packaging

Installation Method

Expansion and Transitions Required

Waterproofing Wet Areas

Radiant Floor

Description

Solid WPC Core

8mm (0.55mm Wear Layer/1.5mm Topper/5mm Waterproof WPC Core/1.5mm IXPE

22 mils (0.50mm)

Unilin Uniclic

Pressed Bevel on 4 sides

5/EIR/4-6

9" Wide x 60" Long

Per Carton: 8 pcs / 29.31 ft.² / 46.20 lbs. / 52 boxes per pallet / 1,523.96 ft.² per pallet

Floating / Glue Down

1/4" expansion and relief against all vertical obstructions. Installation exceeding 1/2" expansion and relief against all vertical obstructions.

1/2" expansion space/use 1/2" foam backer rod and 100% silicone filled in all expansion gaps, and transitions. With this product no floor drains are allowed

Installation Approved Over Embedded Systems Only

Material Classification:

Test Methods		Results
ASTM F2199	Dimensional Stability W/L	≤0.2%
ASTM F2199	Dimensional Stability Curling/Bowing	≤2mm
ASTM F2055	Squareness	≤0.25mm
ASTM F1914	Residual Indentation	≤0.18mm
ASTM F970-17	Static Load	≤0.13mm
ASTM E648	Flooring Radiant Panel	Class1
ASTM D2047	Slip Resistance	>0.5
ASTM E492	Acoustic IIC	60
ASTM E90	Acoustic STC	65
ASTM F1515	Resistance to Light	ΔE* < 8
ASTM F925	Chemical Resistance	
ASTM F1514	Resistance to Heat	ΔE* < 8
ASTM		
ASTM		

Environmental Data

Indoor Air Quality

LEED Scoreboard

Warranty

Description

Limited Lifetime Residential

10 - Year Medium Commercial