

AFTER INSTALLATION

- Install moldings and other aesthetic parts (when applicable).
- Clean the floor and make sure to remove any trace of glue residues.
- For glued installation, limit traffic and moving of furniture on the floor for the recommended duration specified by the glue manufacturer, typically 24 hours.
- Let the floor breathe. Do not cover with a non-porous material like plastic, rubber or vinyl.

CUSTOMER OBLIGATIONS REGARDING THE MAINTENANCE OF A SOLID WOOD FLOOR

- Maintaining the relative humidity level in your house; refer to the table of Annex A “MANDATORY INSTALLATION CONDITIONS BY PRODUCT TYPE”;
- Immediately wipe away any spills;
- Sweep or vacuum regularly;
- Clean your floor with product specifically designed for it;
- Lightly spray the cleaning product on a dry mop or sweeper. Never pour a cleaning product directly on your floor;
- Never clean your floor with a wet mop;
- Install a small rug or a door mat in front of every entrance in order to protect your floor from abrasions and humidity; regularly clean and vacuum those rugs/mats;
- Install small felt pads – or other soft, protective material – under furniture legs to protect the floor from abrasion and dents; replace them regularly by new ones. Do not use hard or plastic covers;
- Never move any heavy objects without protecting your floor. Should you have to move a heavy object, put the object on an upside down clean rug or carpet, and gently slide it across the floor;
- Never use wax, oil-based detergents or other household cleaning products on your floor. These products could damage the lustre/finishing of your floor or make them fade; they are also likely to leave a greasy film on the floor that will make it slippery and hard to clean.