



GOBI JEEP JL ROOF RACK WITH SOFT TOP




GOBI JEEP JL ROOF RACK WITH SOFT TOP



GOBI JEEP JL ROOF RACK WITH SOFT TOP



Fully loosen all 4 lower rear isolator screws both passenger and driver sides as shown



A

Attach Quick release tether to roof rack forward cross bar (A) as shown above

Pull tether tight around roof rack cross bar (A)

A



B


Wrap opposite end of tether to light bar (B) as shown




Secure tether swival hook to "D" ring as shown

Swival hook

"D" Ring





B

Safety Pin

Disconnect safety pin and hang forward of light bar (B)



Support plate (E)

Safety plate (C)

Knob (F)

Slide safety plate (C) away from roof rack support plate (E) and secure in place with knob (F) both driver and passenger sides



Pull back on roof rack and let hang from tether as shown



Gobi rack pulled back for soft top retraction

Unlatch soft top from inside and push back as shown



Gobi rack pulled back for soft top retraction



Gobi rack pulled back for soft top retraction



**Remove rear window for soft
top retraction**



**Remove driver side window for
soft top retraction**



**Remove passenger side window
for soft top retraction**



Retract complete soft top





Full soft top retraction

Return Gobi rack back down behind light bar and secure in place



Gobi rack returned to secured position behind light bar



Gobi rack returned back down to secured position behind light bar





Gobi rack and soft top returned back to covered position and secured in place under 5 minutes