

## MODEL DHH20-14SDFX

### EXPLOSION PROOF FREEZER -15°C TO -25°C

<b>Capacity [ Cu. Ft. ]</b>	<b>14 Cu. Ft.</b>
<b>Capacity [ Liters ]</b>	<b>396 Liters</b>
<b>Temperature Range [ °C ]</b>	<b>-15°C to -25°C</b>
<b>Temperature Range [ °F ]</b>	<b>5°F to -13°F</b>

Dimensions	Width x Depth x Height
Exterior [ Inches ]	23.5" x 24.5" x 73"
Interior [ Inches ]	19" x 17.5" x 63.75"
Exterior [ Centimeters ]	60 x 62 x 185
Interior [ Centimeters ]	48 x 44 x 162

Compressor	Hermetic Compressor
Air Circulation	Gravity Flow
Defrost Method	Manual
Refrigerant	R290
Exterior	Painted Steel
Interior	Painted Steel
Insulation	High Density Urethane
Lockable Door	1 Door, Keyed Lock
Door Material	Insulated Steel
Leveling Legs	4
Storage	6 Fixed Shelves
Shipping Weight	195 lbs.

#### Electrical

Voltage:	115 Volts 60 Hertz 1 Phase
Amperage Line   Running	15 Amp Dedicated   3.5A
Electrical Plug	Not Supplied ( Hardwire )
Certification(s)	ETL Listed

#### Controller

Display Type	Microprocessor, Digital
Alarms	High/Low Temp
Min / Max Temperature	Display and Reset
Alarm Relay	Dry Contacts

IMAGE BELOW DOES NOT SHOW OPTIONAL ACCESSORIES



» Meets NFPA / OSHA Guidelines for Hazardous Locations Class 1, Division II, Group C & D

**Warranty** 2 Years Parts & Labor.