AC-MC-FMC Fittings Zinc Die Cast

Connectors

TYPE: One Screw, Saddle

 FOR: Flexible Metal Conduit, Reduced Wall Flexible Metal Conduit, Armored & Metal Clad Cable, MCI, & MCI-A
MATERIAL: Zinc Die Cast
FINISH: Vibratory

APPLICATIONS:

- Used to connect two pieces of Non-Metallic, Armored or Metal Clad Cable to a 1/2" knockout to a box or enclosure
- Used to connect Steel or Aluminum FMC, AC, MC Cable and Aluminum MCC and MCI-A Cable to a box or enclosure (Armored Cable bushing required for FMC)
- For use in dry locations only

FEATURES:

- Includes (1) Tri-combination head screw applicable with Slotted, Square-Recess, and Phillips screwdrivers
- Part Number 23705 includes Zinc Electro-Plated Steel Saddle

COMPLIANCE:







23705


23700, 10-30

Part No.	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(Ibs)/ 100pcs	
23700	3/8" (1/2" KO)	50	500	8	
23710	1/2"	25	250	13	
23720	3/4"	20	200	20	
23730	1"	10	100	29	
With Steel Saddle					

23705	3/8" (1/2" KO)	50	500	9

NOMINAL DIMENSIONS (Inches):

Part No.	A	B (Min)	B (Max)
23700	0.93	0.400	0.500
23705	0.93	0.400	0.500
23710	1.38	0.660	0.990
23720	1.5	0.700	1.150
23730	1.642	1.100	1.40



23700, 10-30

23705



Electrical Resource International 440.878.1199 www.electrical-resource.com

© Copyright 2018-19 EMCO Electric International, LLC./dba ERI. All Rights Reserved. All specifications are subject to change without notice.