

# LIQUID TIGHT Fittings

## Zinc Die Cast

### Connectors

**TYPE:** Liquid Tight, Straight  
**MATERIAL:** Zinc Die Cast  
**FINISH:** Vibratory

#### APPLICATIONS:

- Used to connect Flexible Metallic Liquid Tight Conduit or Type B Flexible Non-Metallic Conduit to a box or enclosure
- For indoor or outdoor locations

#### FEATURES:

- Includes sealing washer & locknut

#### COMPLIANCE:



File No.:  
E244047




Part No	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
24200	*3/8"	25	250	20
24210	1/2"	25	250	17
24220	3/4"	10	100	25
24230	1"	5	50	44
24240	1-1/4"	5	50	67
24250	1-1/2"	-	10	92
24260	2"	-	5	140
24265	2 1/2"	-	1	221
24270	3"	-	1	284
24275	3-1/2"	-	1	360
24280	4"	-	1	411

\*1/2" K.O.

#### NOMINAL DIMENSIONS (Inches):

Trade Size	A	B	C	Thread Spec NPT
3/8"	1.06	1.45	0.50	14
1/2"	1.06	1.47	0.50	14
3/4"	1.41	1.48	0.56	14
1"	1.70	1.80	0.59	11-1/2
1-1/4"	2.19	1.88	0.67	11-1/2
1-1/2"	2.41	2.17	0.73	11-1/2
2"	3.03	2.28	0.66	11-1/2
2 1/2"	3.63	3.31	1.00	8
3"	3.38	3.50	1.05	8
3-1/2"	3.97	3.63	1.13	8
4"	5.55	3.63	1.16	8



Electrical Resource International  
 440.878.1199  
[www.electrical-resource.com](http://www.electrical-resource.com)