

BX - FLEX - MC Conduit Fittings


Zinc Die Cast



Part No	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt (lbs)/ 100pcs
25804	3/8" (1/2" KO)	50	500	5

NOMINAL DIMENSIONS (Inches):

A	B	C
1.535	0.2755	0.9803




CABLE SPECIFICATIONS:

AL & STEEL AC	AL & STEEL MC/MCI-A/HCF	AL & STEEL FMC/RWFMC
14-2 to 10-3	14-2 to 10-3	3/8"

Snap-In & You're Connected!



Feed wires through fitting.
Snap FMC into fitting.



Snap fitting into box.
Press tabs to remove.



BX Connectors

TYPE: Double Snap-In, Straight, Insulated
FOR: FMC, BX (AC) or MC Cable
BODY MATERIAL: Zinc Die Cast
BODY FINISH: Vibratory
BUSHING: Polycarbonate
SPRING: Electro-Plated, Hardend Steel

APPLICATIONS:

- Used to connect Flexible Metal Conduit, Armored or Metal Clad Cable to a steel box, load center, or other metal enclosure
- For use in dry locations only

FEATURES:

- One piece design
- No tool installation-Reduces labor and time
- Removabe-Reusable without tools
- Secured, pre-assembled anti-short bushing
- 105° C rated throat liners

COMPLIANCE:



Electrical Resource International
 440.878.1199
www.electrical-resource.com