

RIGID Conduit Bodies with Cover & Gasket

TYPE: C, Threaded

BODY MATERIAL: Copper Free Aluminum

COVER MATERIAL: Aluminum with Neoprene Gasket

FINISH: Powder Coated

APPLICATIONS:

- Provides access inside raceways for wire pulling, splicing, inspection, and maintenance

FEATURES:

- Suitable for use in wet locations
- Suitable for use in cement
- NPT tapered hubs

COMPLIANCE:




File No.:
E314478, E244047



Part No	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
81110	1/2"	10	100	29
81120	3/4"	10	50	44
81130	1 "	5	25	66
81140	1-1/4"	2	10	92
81150	1-1/2"	2	10	114
81160	2 "	1	5	255
81165	2-1/2 "	-	1	517
81170	3"	-	1	627
81175	3-1/2"	-	1	1012
81180	4"	-	1	902

NOMINAL DIMENSIONS (Inches):

Trade Size	A	B	C
1/2"	4.825	1.330	1.687
3/4"	5.646	1.552	1.900
1"	6.467	1.747	2.193
1-1/4"	8.268	2.491	3.008
1-1/2"	8.268	2.491	3.008
2"	10.232	3.123	3.736
2-1/2"	13.102	4.444	4.437
3"	13.067	4.459	4.933
3-1/2"	16.236	5.590	5.976
4"	16.236	5.59	5.976



Electrical Resource International
440.878.1199
www.electrical-resource.com