

RIGID Conduit Bodies with Cover & Gasket

TYPE: T, Threaded

BODY MATERIAL: Copper Free Aluminum

COVER MATERIAL: Aluminum with Neoprene Gasket

FINISH: Powder Coated

APPLICATIONS:

- Provides access inside raceways for wire pulling, splicing, inspection, and maintenance
- Used to make bends in conduit systems
- Used to change direction of conduit runs

FEATURES:

- Suitable for use in wet locations
- Suitable for use in cement
- NPT tapered hubs

COMPLIANCE:




File No.:
E314478, E244047



Part No	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
81610	1/2"	10	100	40
81620	3/4"	10	50	44
81630	1 "	5	25	41
81640	1-1/4"	2	10	114
81650	1-1/2"	2	10	92
81660	2"	1	5	233
81665	2-1/2"	-	1	847
81670	3"	-	1	847
81675	3-1/2"	-	1	1122
81680	4"	-	1	1012

NOMINAL DIMENSIONS (Inches):

Trade Size	A	B	C
1/2"	4.825	2.089	1.687
3/4"	5.646	2.241	1.900
1"	6.467	2.523	2.193
1-1/4"	8.268	3.45	3.008
1-1/2"	8.268	3.46	3.008
2"	10.232	4.089	3.736
2-1/2"	13.102	5.85	4.437
3"	13.067	5.85	4.933
3-1/2"	16.236	7.648	5.976
4"	16.236	7.648	5.976



Electrical Resource International
440.878.1199
www.electrical-resource.com