E.M.T. Conduit Fittings Aluminum

Combination Conduit Bodies for EMT & RIGID/IMC with Cover & Gasket

TYPE: XLSLB, Threaded for Rigid/IMC, Set Screw for EMT BODY MATERIAL: Copper Free Aluminum COVER MATERIAL: Aluminum with Neoprene Gasket FINISH: Powder Coated

APPLICATIONS:

- Provides access inside raceways for wire pulling, splicing, inspection, and maintenance
- Used to make bends in conduit systems
- · Used to change direction of conduit runs

FEATURES:

- Suitable for use in wet locations
- Suitable for use in cement
- NPS tapered hubs


COMPLIANCE:



Part No	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(Ibs)/ 100pcs
81219	1/2"	10	100	29
81229	3/4"	10	50	44
81239	1 "	5	25	66
81249	1-1/4"	2	10	92
81259	1-1/2"	2	10	114
81269	2"	1	5	255

NOMINAL DIMENSIONS (Inches):

Trade Size	A	в	с
1/2"	3.165	1.378	1.620
3/4"	3.585	1.700	1.931
1 "	4.235	1.932	2.139
1-1/4"	5.415	2.426	2.566
1-1/2"	6.105	2.598	2.598
2"	6.635	3.104	3.080





Electrical Resource International 440.878.1199 www.electrical-resource.com

© Copyright 2018-19 ELECTRICAL RESOURCE INTERNATIONAL, LLC. All Rights Reserved. All specifications are subject to change without notice.