

E.M.T. Conduit Fittings


Aluminum



Part No.	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt (lbs) / 100pcs
81519	1/2"	10	100	29
81529	3/4"	10	50	44
81539	1 "	5	25	66
81549	1-1/4"	5	20	92
81559	1-1/2"	2	20	114
81569	2"	1	5	255

NOMINAL DIMENSIONS (Inches):

Trade Size	A	B	C
1/2"	4.359	2.015	1.412
3/4"	4.972	2.299	1.655
1 "	5.819	2.427	1.894
1-1/4"	7.795	3.391	2.685
1-1/2"	7.807	3.412	2.685
2"	9.850	4.082	3.425



Combination Conduit Bodies for EMT & RIGID/IMC with Cover & Gasket

TYPE: LR, Threaded for Rigid/IMC, Set Screw for EMT
BODY MATERIAL: Copper Free Aluminum
COVER MATERIAL: Aluminum with Neoprene Gasket
FINISH: Powder Coated

APPLICATIONS:

- Provides access inside raceways for wire pulling, splicing, inspection, and maintenance
- Used to make bends in conduit systems
- Used to change direction of conduit runs

FEATURES:

- Suitable for use in wet locations
- Suitable for use in cement
- NPS tapered hubs

COMPLIANCE:



File No.:
E314478, E244047



Electrical Resource International
440.878.1199
www.electrical-resource.com