



Connectors

TYPE: Double "Snap-In", 90°, Insulated
FOR: Flexible Metal Conduit, Armored & Metal Clad Cable
BODY MATERIAL: Zinc Die Cast with Steel Band
BODY FINISH: Vibratory
BUSHING: Polycarbonate
SPRING: Electro-Plated, Hardend Steel

APPLICATIONS:

- Used to connect Flexible Metal Conduit, Armored Cable, Metal Clad cable to a steel box, load center, or other metal enclosure
- For use in dry locations only

FEATURES:

- One piece design
- No tool installation reducing time and labor
- Removable & Reusable
- Secured, preassembled anti-short bushing
- 105° C rated throat liner

COMPLIANCE:




Electrical Resource International
 440.878.1199
www.electrical-resource.com



Part No	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt (lbs) / 100pcs
25001	3/8" (1/2" KO)	25	250	10
25011	1/2"	25	250	15

NOMINAL DIMENSIONS (Inches):

Part No	A	B	C
25001	1.67	2.06	1.37
25011	1.93	2.06	1.67



CABLE SPECIFICATIONS:

Part No	AL & STEEL AC	AL & STEEL MC/MCI-A/MCO-HCF	AL & STEEL RWFMC
25001	14-2 to 10-3	14-2 to 10-4	3/8"
25011	8-2 to 8-3	8-2 to 8-3	3/8"

Snap-In & You're Connected!

