

Bushings

TYPE: Non-Metallic, Knock Out, "Snap-In"

FOR: Flexible Metal Conduit, Armored & Metal Clad Cable

MATERIAL: Nylon 6/6

FINISH: Natural

APPLICATIONS:

- Used to protect wires/cables from rough edges

FEATURES:

- Locking fingers snap into holes
- Multiple locking steps for panel thickness up to .125"
- Push back tolerance of 35lbs
- Flammability Rating: 94V-2
- Temperature Rating: -4°F (18°C) to 221°F (105°C)


COMPLIANCE:



Part No	Trade Size	Bag	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
90810	1/2"	100	10	55
90820	3/4"	100	10	75
90830	1"	100	10	95
90840	1-1/4"	50	10	85
90850	1-1/2"	25	10	60
90860	2"	25	10	118
90865	2-1/2"	25	10	135
90870	3"	10	10	63
90880	4"	10	10	65

NOMINAL DIMENSIONS (Inches):

Part No	Mounting Hole Dia.	A	B	C
90810	0.875	0.687	0.955	0.455
90820	1.093 / 1.125	0.812	1.220	0.450
90830	1.375	1.000	1.470	0.450
90840	1.750	1.375	1.880	0.460
90850	2.000	1.640	2.130	0.464
90860	2.500	1.970	2.650	0.714
90865	3.000	2.530	3.180	0.690
90870	3.500	2.940	3.660	0.720
90880	4.000	3.470	4.150	0.720



Electrical Resource International
440.878.1199
www.electrical-resource.com