

# E.M.T. Conduit Fittings


Zinc Die Cast



Part No.	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
20110	1/2"	50	500	11
20120	3/4"	25	250	16
20130	1"	50	250	25
20140	1-1/4"	-	25	43
20150	1-1/2"	-	25	54
20160	2"	-	15	76
20165	2-1/2"	-	12	190
20170	3"	-	12	300
20175	3-1/2"	-	10	330
20180	4"	-	6	360

## NOMINAL DIMENSIONS (Inches):

Trade Size	A		B	C	
	Standard	Insulated		Standard	Insulated
1/2"	1.256	1.315	0.965	0.433	0.492
3/4"	1.209	1.268	1.264	0.433	0.492
1"	1.575	1.643	1.516	0.547	0.606
1-1/4"	1.618	1.697	1.906	0.575	0.654
1-1/2"	1.874	1.953	2.276	0.622	0.701
2"	2.146	2.225	2.610	0.765	0.835
2-1/2"	2.610	2.689	3.311	1.004	1.083
3"	2.790	2.869	4.21	1.004	1.083
3-1/2"	2.770	2.849	5.060	0.940	1.019
4"	2.839	2.918	5.350	1.087	1.166



## EMT Connectors

**TYPE:** Compression  
**MATERIAL:** Zinc Die Cast  
**FINISH:** Vibratory

### APPLICATIONS:

- Used to connect EMT conduit to steel outlet boxes, metal enclosures, or load centers
- Sizes 2-1/2" - 4" are cULus listed for use with EMT, RIGID and IMC conduit
- For use in dry locations
- For Canada: Sizes 1/2" - 4" are cUL listed rain tight, and may be used for wet and dry locations
- Concrete-tight

### FEATURES:

- Available with or without 105° C rated insulated throat liner
- Hex nut for wrench installation and tightening
- Zinc Die Cast locknut

### COMPLIANCE:



File No.:  
E232667, E244047



Electrical Resource International  
 440.878.1199  
[www.electrical-resource.com](http://www.electrical-resource.com)