

E.M.T. Conduit Fittings


Zinc Die Cast



Part No.	Trade Size		Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt (lbs) / 100pcs
	Standard	Insulated			
21110	31110	1/2"	50	500	7
21120	31120	3/4"	25	250	10
21130	31130	1"	50	250	15
21140	31140	1-1/4"	-	25	29
21150	31150	1-1/2"	-	25	40
21160	31160	2"	-	20	54
21165	31165	2-1/2"	-	12	83
21170	31170	3"	-	12	100
21175	31175	3-1/2"	-	6	128
21180	31180	4"	-	6	156

NOMINAL DIMENSIONS (Inches):

Trade Size	A		B		C
	Standard	Insulated	Standard	Insulated	
1/2"	1.157	1.196	0.382	0.421	0.933
3/4"	1.378	1.417	0.366	0.405	1.169
1"	1.504	1.543	0.500	0.539	1.421
1-1/4"	1.969	2.008	1.535	1.574	1.823
1-1/2"	2.260	2.299	1.768	1.807	2.067
2"	2.563	2.602	2.260	2.267	2.524
2-1/2"	3.090	3.149	1.047	1.106	3.295
3"	3.374	3.433	1.059	1.118	3.909
3-1/2"	3.460	3.519	1.059	1.118	4.460
4"	3.759	3.818	1.110	1.169	4.881



EMT Connectors

TYPE: Set Screw
MATERIAL: Zinc Die Cast
FINISH: Vibratory

APPLICATIONS:

- Used to connect EMT conduit to steel outlet boxes, metal enclosures, or load centers
- Sizes 2-1/2" - 4" are cULus listed for use with EMT, Rigid, and IMC conduit
- For use in dry locations
- Concrete-tight when taped
- For Canada: concrete-tight

FEATURES:

- Available with or without 105° C rated insulated throat liner
- Male hub threads - NPSM
- Zinc Die Cast locknut, staked tri-combination head set screws applicable with Phillips, Slotted, or Square-Recess screwdrivers
- Sizes 1/2" - 2" include (1) set screw
- Sizes 2-1/2" - 4" includes (2) set screws

COMPLIANCE:



File No.:
E232667, E244047



Electrical Resource International
 440.878.1199
www.electrical-resource.com