

E.M.T. Conduit Fittings


Steel



A	Standard	Insulated	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
40114	50114		1/2"	50	500	11
40124	50124		3/4"	25	250	16
40134	50134		1"	25	100	25
40144	50144		1-1/4"	5	25	43
40154	50154		1-1/2"	-	20	54
40164	50164		2"	-	20	76
40169	50169		2-1/2"	-	10	190
40174	50174		3"	-	10	300
40179	50179		3-1/2"	-	10	330
40184	50184		4"	-	10	360

NOMINAL DIMENSIONS (Inches):

Trade Size	A	B	C
1/2"	0.689	0.500	1.125
3/4"	0.750	0.500	1.375
1"	0.846	0.562	1.687
1-1/4"	1.687	1.012	2.062
1-1/2"	1.717	1.062	2.25
2"	1.875	1.125	2.75
2-1/2"	1.968	1.562	3.625
3"	2.689	1.562	4.25
3-1/2"	2.812	1.812	4.687
4"	2.812	1.812	5.187



EMT Rain-tight Connectors

TYPE: Compression
MATERIAL: Steel
FINISH: Zinc Electro Plated

APPLICATIONS:

- Used to connect EMT conduit to boxes or enclosures
- Sizes 2-1/2" - 4" cULus listed for EMT, RIGID, and IMC conduit
- Rain-tight, for use in wet locations
- Concrete-tight

FEATURES:

- Available with or without insulated throat
- Insulated throat prevents cable stripping
- Male hub threads NPS
- Blue anadize compression nut indicates rain-tight application

COMPLIANCE:



Electrical Resource International
 440.878.1199
www.electrical-resource.com