



Cable & Conduit Pipe Strut Clamps

TYPE: Universal Type, One Piece

MATERIAL: Steel

FINISH: Galvanized

APPLICATIONS:

- Used to attach EMT or RIGID conduit along slot side of strut channels.

FEATURES:

- Preassembled, "break-a-part" design with screw and built-in, internal speed thread minimizes less dropped parts and more efficient installation
- Tri-Combination Hex head bolt suitable for wrench, screwdriver or nutdriver installations
- Ribbed for extra rigidity & strength

COMPLIANCE:



File No.:
E313499



Electrical Resource International
440.878.1199
www.electrical-resource.com



1/2" - 2"



2-1/2" - 4"

Part No	EMT RIGID IMC Size	O.D. Range (in)	Load Rating SF3 (lbs)	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
49510	5/16"-1/2"	0.706 - 0.804	300	100	9
49520	3/4"	0.922 - 1.050	300	100	11
49530	1"	1/163 - 1.315	300	100	12
49540	1-1/4"	1.510 - 1.660	300	100	14
49550	1-1/2"	1.740 - 1.900	300	100	14
49560	2"	2.197 - 2.375	300	50	16
49565	2-1/2"	2.875	600	50	26
49570	3"	3.500	600	25	31
49575	3-1/2"	4.000	600	25	34
49580	4"	4.500	600	25	37

*The load rating published includes a safety factor of 3.0
(Safety Factor = Ratio of Ultimate Load to the Design Load)



Assembled