

## AC-MC-FMC Fittings Zinc Die Cast



### Duplex Connectors FMC, AC & MC Cable

**TYPE:** Double "Snap-In", Duplex, Insulated  
**FOR:** FMC, AC & MC Cable  
**BODY MATERIAL:** Zinc Die Cast with Steel Band  
**BODY FINISH:** Vibratory  
**BUSHING:** Polycarbonate  
**SPRING:** Electro-Plated, Hardend Steel

#### APPLICATIONS:

- Used to connect two sets of Flexible Metal Conduit, Armored or Metal Clad Cable to a steel box, load center, or other metal enclosure
- For use in dry locations only

#### FEATURES:

- One piece design
- No tool installation-Reduces labor and time
- Removable & Reusable
- Secured, pre-assembled anti-short bushing
- 105° C rated throat liners

#### COMPLIANCE:



Electrical Resource International  
 440.878.1199  
[www.electrical-resource.com](http://www.electrical-resource.com)



Part No	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt (lbs) / 100pcs
22804	3/8" (1/2" KO)	25	250	13

#### NOMINAL DIMENSIONS (Inches):

A	B	C
2.10	1.58	0.708

#### CABLE SPECIFICATIONS:

AL & STEEL AC	AL & STEEL MC/MCI-A/HCF	AL & STEEL RWFMC
14-2 to 10-3	14-2 to 10-3	3/8"

### Snap-In & You're Connected!

