

Connectors

TYPE: 90° Squeeze
FOR: FMC, AC & MC Cable
MATERIAL: Zinc Die Cast
FINISH: Vibratory
STRAP MATERIAL: Zinc Plated Steel

APPLICATIONS:

- Used to connect Flexible Metal Conduit, Armored Cable, Metal Clad cable through a 3/8" or 1/2" knock-out in a steel box, load center, or other metal enclosure where a 90° angle is required
- For use in dry locations

FEATURES:

- Includes (2) staked Tri-Combination head set screw applicable with Phillips, Slotted, or Square-Recess screwdrivers

COMPLIANCE:



File No.:
E232666



Electrical Resource International
www.electrical-resource.com
 440.878.1199



Part No.		Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
Standard	Insulated				
25000	35000	3/8"	50	500	9
25010	35010	1/2"	25	250	14
25020	35020	3/4"	10	100	20
25030	35030	1"	5	50	38
25040	35040	1-1/4"	10	50	51
25050	35050	1-1/2"	-	10	113
25060	35060	2"	-	5	123
25065	35065	2-1/2"	-	5	400
25070	35070	3"	-	2	500
25075	35075	3-1/2"	-	1	1300
25080	35080	4"	-	1	1900

NOMINAL DIMENSIONS (Inches):

Trade Size	A	B		C	
		Min	Max	Standard	Insulated
3/8"	1.752	0.43	0.72	0.35	0.409
1/2"	2.122	0.64	1.03	0.35	0.409
3/4"	2.346	0.76	1.15	0.44	0.499
1"	2.768	1.09	1.73	0.543	0.602
1-1/4"	3.890	1.34	1.97	0.594	0.674
1-1/2"	6.008	1.65	2.61	0.689	0.769
2"	6.008	1.54	2.54	0.701	0.781
2-1/2"	6.795	2.45	2.98	0.843	0.923
3"	7.886	2.93	3.45	0.827	0.907
3-1/2"	9.400	3.28	3.95	0.941	1.021
4"	9.783	3.68	4.43	0.941	1.021

