

AC-MC-FMC Fittings


Zinc Die Cast




Part No.		Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
Standard	Insulated				
25200	35200	3/8" (1/2" KO)	50	500	7
25210	35210	1/2"	25	250	10
25220	35220	3/4"	25	250	13
25230	35230	1"	10	100	20
25240	35240	1-1/4"	10	100	29
25250	35250	1-1/2"	5	50	39
25260	35260	2"	10	50	46
25265	35265	2-1/2"	-	10	84
25270	35270	3"	-	10	147
25275	35275	3-1/2"	-	1	488
25280	35280	4"	-	1	660

NOMINAL DIMENSIONS (Inches):

Trade Size	A		B	C
	Standard	Insulated		
3/8"	1.146	1.206	0.512	1.141
1/2"	1.437	1.497	0.492	1.370
3/4"	1.575	1.635	0.476	1.574
1"	1.760	1.820	0.571	1.866
1-1/4"	1.874	1.954	0.587	2.145
1-1/2"	2.008	2.934	0.610	2.519
2"	2.087	2.167	0.606	3.011
2-1/2"	2.854	2.954	0.866	3.866
3"	2.236	0.336	0.866	4.354
3-1/2"	3.840	3.940	0.902	4.788
4"	4.055	4.155	0.902	5.303



Sizes 3/8" - 2"



Sizes 2-1/2" - 4"

Connectors

TYPE: Straight-Squeeze
FOR: FMC, AC & MC Cable
MATERIAL: Zinc Die Cast
FINISH: Vibratory

APPLICATIONS:

- Used to connect Flexible Metal Conduit and steel Armored cable to a box or enclosure
- Size 3/8" can also be used with steel and aluminum Metal Clad cable
- For use in dry locations only

FEATURES:

- Sizes 3/8" - 2" include (1) Tri-Combination head screws applicable with Slotted, Square-Recess, and Phillips screwdrivers
- Sizes 2-1/2" - 4" include (1) Tri-Combination head screws applicable with Slotted, Square-Recess, and Phillips screwdrivers
- Available with or without insulated throat liner

COMPLIANCE:



File No.:
E232666



Electrical Resource International
www.electrical-resource.com
 440.878.1199