

AC-MC-FMC Fittings


Zinc Die Cast



Part No.		Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
Standard	Insulated				
25400	35400	3/8" (1/2" KO)	50	500	5
25410	35410	1/2"	25	250	5
25420	35420	3/4"	25	250	9
25430	35430	1 "	10	100	15
25440	35440	1-1/4"	10	100	24
25450	35450	1-1/2"	5	50	32
25460	35460	2 "	5	50	59

NOMINAL DIMENSIONS (Inches):

Trade Size	A		B
	Standard	Insulated	
3/8"	1.303	1.363	0.906
1/2"	1.366	1.426	0.913
3/4"	1.614	1.674	1.126
1 "	1.925	1.985	1.366
1-1/4"	2.142	2.222	1.744
1-1/2"	2.413	2.493	2.098
2 "	2.559	2.639	2.650



Connectors

TYPE: Screw-In
FOR: Flexible Metal Conduit (FMC)
MATERIAL: Zinc Die Cast
FINISH: Vibratory

APPLICATIONS:

- Used to connect Flexible Metal Conduit to steel boxes, load centers or other metal enclosures
- For use in dry locations only

FEATURES:

- Includes Zinc Die Cast locknut
- Screws into conduit for easy installation
- Available with or without insulated throat liner
- Insulated throat liner is 105°C rated

COMPLIANCE:



File No.:
E244047



Electrical Resource International
www.electrical-resource.com
440.878.1199