

AC-MC-FMC Fittings


Zinc Die Cast



Part No	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
25801	3/8" (1/2" KO)	100	1000	5

NOMINAL DIMENSIONS (Inches):

A	B	C
1.47	0.829	0.935




CABLE SPECIFICATIONS:

Steel AC Cable Range (Nominal OD)	Steel MCI Cable Range (Nominal OD)
14-2 to 10-2	14-2 to 10-3
0.460 - 0.598	0.469 - 0.600

Snap-In & You're Connected!



Insert wires & FMC into fitting.



Snap fitting into box.



Cable Connectors

FMC, AC & MC Cable

TYPE: Set Screw

FOR: Flexible Metal Conduit, Armored & Metal Clad Cable

MATERIAL: Zinc Die Cast with Steel Band

FINISH: Vibratory

APPLICATIONS:

- Used to connect Flexible Metal Conduit, Armored or Metal Clad Cable to a steel box, load center or other metal enclosure
- For use in dry locations only

FEATURES:

- One piece design
- Easy installation reducing labor and time
- Removable-Reusable
- Includes (1) Tri-Combination head set screw applicable with Phillips, Slotted, and Square-Recess screwdrivers

COMPLIANCE:



Electrical Resource International
440.878.1199
www.electrical-resource.com