

RIGID & IMC Conduit Fittings


Zinc Die Cast



Part No.	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
36610	1/2"	100	1000	20
36620	3/4"	100	1000	30
36630	1"	50	500	40
36640	1-1/4"	25	250	52
36650	1-1/2"	25	250	70
36660	2"	25	250	95
36665	2-1/2"	-	50	190
36670	3"	-	25	240
36675	3-1/2"	-	25	300
36680	4"	-	10	340

NOMINAL DIMENSIONS (Inches):

Trade Size	A	B
1/2"	1.406	1.406
3/4"	1.661	1.539
1"	1.949	1.752
1-1/4"	2.409	1.689
1-1/2"	2.693	1.713
2"	3.201	1.831
2-1/2"	3.685	2.594
3"	4.385	2.614
3-1/2"	4.880	2.440
4"	5.437	2.559



Water-Tight Hubs

TYPE: Insulated

MATERIAL: Zinc Die Cast

FINISH: Vibratory

APPLICATIONS:

- Used to connect threaded RIGID/IMC conduit to an enclosure or load center requiring a water-tight joint at knockouts or slip-fit holes
- For wet or dry locations

FEATURES:

- Flame retardant, insulated throat prevents cable stripping
- Includes insulated throat liner
- Includes "O-Ring" providing an oil, dust, and rain-tight seal
- Includes over-sized Zinc Die Cast locknut providing a vibration free application and positive grounding

COMPLIANCE:



File No.:
E244047



Electrical Resource International
www.electrical-resource.com
440.978.1199