

RIGID & MC Conduit Fittings

Zinc Die Cast

Water-Tight Hubs with Bonding Screw

TYPE: Insulated
MATERIAL: Zinc Die Cast
FINISH: Vibratory

APPLICATIONS:

- Used to connect threaded RIGID/IMC conduit to an enclosure or load center requiring a water-tight joint at knockouts or slip-fit holes
- For wet or dry locations

FEATURES:

- Flame retardant, insulated throat prevents cable stripping
- Available with or without insulated throat liner
- Includes "O-Ring" providing an oil, dust, and rain-tight seal
- Includes over-sized Zinc Die Cast locknut providing a vibration free application and positive grounding
- Includes staked combination head screw applicable with Phillips, Slotted or Square-Recess screwdrivers

COMPLIANCE:



Electrical Resource International
www.electrical-resource.com
 440.978.1199



Part No.	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
36613	1/2"	100	1000	13
36623	3/4"	100	1000	17
36633	1"	50	500	25
36643	1-1/4"	25	250	36
36653	1-1/2"	25	250	48
36663	2"	25	250	65
36668	2-1/2"	-	50	85
36673	3"	-	25	136
36678	3-1/2"	-	25	179
36683	4"	-	10	207

NOMINAL DIMENSIONS (Inches):

Trade Size	A	B
1/2"	1.406	1.406
3/4"	1.661	1.539
1"	1.949	1.752
1-1/4"	2.409	1.689
1-1/2"	2.693	1.713
2"	3.201	1.831
2-1/2"	3.685	2.594
3"	4.385	2.614
3-1/2"	4.880	2.440
4"	5.437	2.559

