

RIGID & IMC Conduit Fittings

Zinc Die Cast

Pull Elbow

RIGID/IMC to RIGID/IMC

TYPE: 90°, Threaded with Cover & Gasket

MATERIAL: Zinc Die Cast with Aluminum Cover and Neoprene Gasket

FINISH: Vibratory

APPLICATIONS:

- Used to connect threaded RIGID/IMC conduit to RIGID/IMC to create a 90° turn in a run when bending conduit is not feasible
- For use in wet or dry locations (RIGID Only)
- May be used with EMT, dry locations only

FEATURES:

- Removable cover promotes easy wire pulling
- Includes Zinc Die Cast locknut, Aluminum cover, Neopr

COMPLIANCE:




File No.:
E244047



Part No	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
37110	1/2"	10	100	28
37120	3/4"	5	50	33
37130	1"	-	25	62
37130	1-1/4"	-	25	91

NOMINAL DIMENSIONS (Inches):

Trade Size	A	B
1/2"	1.311	0.992
3/4"	1.385	1.260
1"	1.961	1.516
1-1/4"	2.303	1.900



Electrical Resource International
www.electrical-resource.com
440.978.1199