

E.M.T. Conduit Fittings

Steel




1-1/4" - 4"

1/2" - 1"

	A	Trade	Pcs/	Pcs/	Wt
Standard	Insulated	Size	Unit Ctn	Ship Ctn	(lbs) /100pcs
41110	51110	1/2"	50	500	10
41120	51120	3/4"	25	250	15
41130	51130	1"	25	100	24
41140	51140	1-1/4"	-	20	45
41150	51150	1-1/2"	-	20	65
41160	51160	2"	-	20	85
41165	51165	2-1/2"	-	10	162
41170	51170	3"	-	10	216
41175	51175	3-1/2"	-	10	250
41180	51180	4"	-	10	275

NOMINAL DIMENSIONS (Inches):

Trade Size	A	B	C
1/2"	0.726	1.459	0.375
3/4"	0.942	1.485	0.375
1"	1.183	1.635	0.440
1-1/4"	1.530	2.325	0.500
1-1/2"	1.760	2.500	0.562
2"	2.217	2.850	0.625
2-1/2"	2.910	3.205	0.769
3"	3.540	3.750	0.915
3-1/2"	4.045	4.000	0.902
4"	4.545	4.250	1.021



EMT Connectors

TYPE: Set Screw

MATERIAL: Steel

FINISH: Zinc Electro Plated

APPLICATIONS:

- Used to connect EMT conduit to boxes or enclosures
- Sizes 2-1/2" - 4" cULus listed for EMT, RIGID, and IMC conduit
- For use in dry locations
- Concrete-tight when taped
- For Canada: concrete-tight

FEATURES:

- Available with or without insulated throat liner
- Insulated throat prevents cable stripping
- Male hub threads NPSM
- Steel locknut
- Staked tri-combination head set screws applicable with Phillips, Slotted or Square-Recess screwdrivers
- Sizes 1/2" - 1" include with 1 set screw
- Sizes 1-1/4" - 4" include 2 set screws

COMPLIANCE:



File No.:
E232667, E244047



Electrical Resource International
440.878.1199
www.electrical-resource.com