

Liquid Tight Connectors

TYPE: Straight, with or without Insulated Throat Liner

MATERIAL: Steel & Malleable

FINISH: Zinc Electro Plated

APPLICATIONS:

- Used to connect flexible metallic liquid tight conduit or Type B flexible non-metallic conduit to a box or enclosure
- For indoor or outdoor locations

FEATURES:

- Liquid tight-water and oil
- Tapered NPT, male hub
- Includes sealing washer & locknut
- Sizes 3/8"-2" Steel
- Sizes 2-1/2"-4" Malleable

COMPLIANCE:




File No.:
E244047



Part	No	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
Standard	Insualted				
44200	54200	3/8"	25	250	20
44210	54210	1/2"	25	250	17
44220	54220	3/4"	10	100	25
44230	54230	1"	5	50	44
44240	54240	1-1/4"	5	50	67
44250	54250	1-1/2"	-	10	92
44260	54260	2"	-	5	140
44265	54265	2 1/2"	-	1	221
44270	54270	3"	-	1	284
44275	54275	3-1/2"	-	1	360
44280	54280	4"	-	1	411

NOMINAL DIMENSIONS (Inches):

Trade Size	A	B	C	Thread Spec NPT
3/8"	1.06	1.45	0.50	14
1/2"	1.06	1.47	0.50	14
3/4"	1.41	1.48	0.56	14
1"	1.70	1.80	0.59	11-1/2
1-1/4"	2.19	1.88	0.67	11-1/2
1-1/2"	2.41	2.17	0.73	11-1/2
2"	3.03	2.28	0.66	11-1/2
2 1/2"	3.63	3.31	1.00	8
3"	3.38	3.50	1.05	8
3-1/2"	3.97	3.63	1.13	8
4"	5.55	3.63	1.16	8



Electrical Resource International
440.878.1199
www.electrical-resource.com