

RIGID & IMC Conduit Fittings


Steel



Part No	Trade Size	Pcs/ Ship Ctn	Wt (lbs) / 100pcs
48210	3/4" x 1/2"	100	4
48215	1" x 1/2"	50	12
48220	1" x 3/4"	50	7
48225	1-1/4" x 1/2"	50	28
48230	1-1/4" x 3/4"	50	21
48235	1-1/4" x 1"	50	13
48240	1-1/2" x 1/2"	50	40
48245	1-1/2" x 3/4"	50	33
48250	1-1/2" x 1"	50	26
48255	1-1/2" x 1-1/4"	50	10
48260	2" x 1/2"	25	77
48265	2" x 3/4"	25	72
48270	2" x 1"	25	64
48275	2" x 1-1/4"	25	41
48280	2" x 1-1/2"	25	30

NOMINAL DIMENSIONS (Inches):

Part No	A	B
48210	0.89	0.630
48215	1.10	0.669
48220	1.10	0.669
48225	1.44	0.709
48230	1.44	0.709
48235	1.44	0.709
48240	1.71	0.709
48245	1.71	0.709
48250	1.71	0.709
48255	1.71	0.709
48260	2.11	0.787
48265	2.11	0.787
48270	2.11	0.787
48275	2.11	0.787
48280	2.11	0.787



Reducing Bushings

MATERIAL: Steel

FINISH: Zinc Electro Plated

APPLICATIONS:

- Used to reduce the entry size of a run of threaded conduit (female hub to male hub)
- For use in dry locations

FEATURES:

- Protects conductor

COMPLIANCE:



File No.:
E248623



Electrical Resource International
www.electrical-resource.com
440.978.1199