

Liquid Tight


Steel & Malleable Iron



Part No	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
54203	3/8"	50	200	17
54213	1/2"	50	200	19
54223	3/4"	25	100	30
54233	1"	-	10	41
54243	1-1/4"	-	10	57
54253	1-1/2"	-	5	72
54263	2"	-	5	101
54268	2-1/2"	-	1	372
54273	3"	-	1	465
54278	3-1/2"	-	1	685
54283	4"	-	1	806

NOMINAL DIMENSIONS (Inches):

Trade Size	A	B	C	D	Thread Spec NPT
3/8"	1.06	1.45	0.50	0.781	14
1/2"	1.06	1.47	0.50	0.781	14
3/4"	1.41	1.48	0.56	0.781	14
1"	1.70	1.80	0.59	0.781	11-1/2
1-1/4"	2.19	1.88	0.67	0.781	11-1/2
1-1/2"	2.41	2.17	0.73	0.781	11-1/2
2"	3.03	2.28	0.66	0.781	11-1/2
2 1/2"	3.63	3.31	1.00	1.17	8
3"	3.38	3.50	1.05	1.17	8
3-1/2"	3.97	3.63	1.13	1.81	8
4"	5.55	3.63	1.16	1.81	8



Liquid Tight Connectors

TYPE: Straight, Insulated, with Ground Lug

MATERIAL: Steel & Malleable Iron

FINISH: Zinc Electro Plated

APPLICATIONS:

- Used to connect flexible metallic liquid tight conduit when installation of a copper or aluminum external bonding jumper is required
- For indoor or outdoor locations

FEATURES:

- Liquid tight-water and oil
- Tapered NPT, male hub
- Includes sealing washer & locknut
- Sizes 3/8"-2" Steel
- Sizes 2-1/2"-4" Malleable
- With insulated Throat Liner

COMPLIANCE:



File No.:
E244047



Electrical Resource International
440.878.1199
www.electrical-resource.com