

## Liquid Tight Connectors

**TYPE:** 90°, Insulated, with Ground Lug  
**MATERIAL:** Steel & Malleable Iron  
**FINISH:** Zinc Electro Plated

### APPLICATIONS:

- Used to connect flexible metallic liquid tight conduit when installation of a copper or aluminum external bonding jumper is required
- For indoor or outdoor locations

### FEATURES:

- Liquid tight-water and oil
- Tapered NPT, male hub
- Includes sealing washer & locknut
- Sizes 3/8"-2" Steel
- Sizes 2-1/2"-4" Malleable
- With insulated Throat Liner

### COMPLIANCE:




File No.:  
E244047



Part No	Trade Size	Pcs/ Unit Ctn	Pcs/ Ship Ctn	Wt(lbs)/ 100pcs
54303	3/8"	25	100	27
54313	1/2"	25	100	31
54323	3/4"	25	100	46
54333	1 "	-	10	76
54343	1-1/4"	-	10	98
54353	1-1/2"	-	5	123
54363	2"	-	5	178
54368	2-1/2 "	-	1	846
54373	3"	-	1	1243
54378	3-1/2"	-	1	1913
54383	4"	-	1	2398

### NOMINAL DIMENSIONS (Inches):

Trade Size	A	B	C	Thread Spec NPT
1/2"	1.44	1.38	0.55	14
3/4"	1.63	1.41	0.56	14
1"	1.88	1.63	0.58	14
1-1/4"	2.13	1.94	0.64	11-1/2
1-1/2"	2.25	2.02	0.66	11-1/2
2"	2.63	2.25	0.77	11-1/2
2-1/2"	3.00	2.47	0.75	11-1/2
3"	5.00	3.34	1.03	8
3-1/2"	4.44	4.78	1.06	8
4"	6.00	5.23	1.19	8



Electrical Resource International  
440.878.1199  
www.electrical-resource.com